

S-Claw Couplings

Australian specification Claw couplings for conveyance of compressed air, water and other non corrosive liquids and gases.

Applications

- * Mining
- * Civil and industrial applications
- * Construction
- * Fire sprinkler systems
- * Municipal water supplies
- * Industrial air reticulation

Material Specifications

- * Spheroidal Graphite Iron,
- * Acid Zinc Plated
- * Nitrile Rubber Gasket



S-Claw Hosetail



BSP S-Claw

| HOSE SIZE N.B. mm | PIPE THREAD B.S.P. | DESCRIPTION | PART No. | A | B | e | D |
|----------------------|-----------------------|-------------------------------------------|--------------|----|-----|----|----|
| 12.5 | | 12,5mm "S" CLAW HOSETAIL WITH SEAT | BS250-12.5S | 40 | 68 | | |
| 25 | | 25mm "S" CLAW HOSETAIL WITH SEAT | BS250-25S | 54 | 95 | | |
| 50 | | 50mm "S" CLAW HOSETAIL WITH SEAT | BS500-50S | 78 | 131 | | |
| • | 1/2" MALE | 1/2" B.S.P.T. "S" CLAW COUPLING WITH SEAT | | | | | |
| • | 1" MALE | 1" B.S.P.T. "S" CLAW COUPLING WITH SEAT | BS250-25BSPT | | | 22 | 55 |
| • | 2" MALE | 2" B.S.P.T. "S" CLAW COUPLING WITH SEAT | BS500-50BSPT | | | 30 | 82 |